



Product Data Sheet

680 Graphite Grease

Description: *680 Graphite Grease* is a water-resistant, calcium-based graphite grease. Ideal for general equipment lubrication where application is exposed to moisture.

Typical Properties:

NLGI Grade	: 1
Graphite	: 10%
Thickener	: Calcium
Penetration (@77°F)	: 310-340
Dropping Point	: 185°F
Color	: Black
Shelf Life	: 1 year from ship date

Method of Use: *680 Graphite Grease* can be applied on a variety of metal surfaces. It is not guaranteed to be compatible with other greases- thoroughly remove old grease before using. Frequent re-lubrication is necessary at elevated temperatures.

Precautions: The customary safeguards employed when storing, handling and application should be employed. To prevent contamination, container should be sealed when not in use. Please refer to Material Safety Data Sheet for proper first aid instructions.

Container Size: 35 lb pails



ASBURY GRAPHITE MILLS, INC.
405 Old Main Street • PO Box 144 • Asbury, New Jersey 08802
Phone: 908.537.2155 • Fax: 908.537.2908
www.asbury.com
Sales Manager: Russell Werkheiser russellw@asbury.com rev 1-1-15

For over 119 years, providing value with quality,
consistency and reliability in all we do!