



ASBURY
C A R B O N S

LUBRICANTS AND SPECIALTY PRODUCTS GROUP

A division of Asbury Carbons, Inc.

Cummings-Moore Graphite Co. • 1646 N. Green Ave. • Detroit, MI 48209
Tel: (313) 841-1615 • Fax: (313) 841-4880 • www.asbury.com

PRODUCT INFORMATION

GRAPHITE WAX STICKS

Description: *Graphite Wax Sticks* are specially formulated lubricant sticks designed to coat, lubricate, and reduce friction on various surfaces.

Physical Properties: Lubricating Solid : Graphite
(As supplied) Sizes Available : 3/4 in. diameter X 6 in. long
2 in. diameter X 10 in. long
Shelf Life : Indefinite

Typical Uses:

- Lubricant for tough grinding and cutting operations – reduces friction and heat while increasing equipment life.
- Coating for dummy blocks and billet ends in aluminum extrusion operations. Also for mold touch-up, slide gate refractory plates, troughs, etc.
- Ideal as a general-purpose lubricant for operations such as drilling, tapping, pipe cutting, etc. Allows pinpoint lubrication to avoid housekeeping problems associated with fluid or grease type lubricants.

Method of Use: *Graphite Wax Sticks* can be hand applied directly to area requiring lubrication – for surface temperatures up to 250°F (121°C). For higher-temperature applications, try our *Dixon Lube Sticks* or *Graph-on Lubricant Sticks*.

Precautions: The customary safeguards employed in storing, handling and application should be employed.

Please refer to Material Safety Data Sheet for proper first aid instructions.

WORLD'S LARGEST PROCESSOR OF GRAPHITES AND OTHER CARBONACEOUS PRODUCTS

Information presented in this product information sheet is considered reliable, but conditions and methods of use, that are beyond our control may modify results and performance. The PDS lists percentages that are guaranteed only following specific agreement between Dixon Lubricants and Specialty Products Group and the customer. They are listed here to indicate approximate physical and chemical analysis. The user assumes the risk and liability for loss, damage or injury arising from the application of the goods furnished.

Revised 3/22/2005